

.25-06 Remington							
Index No.	Wt. (grs.)	Bullet Style			Primer No.	Barrel Length	
R25062	100	Pointed Soft Point Core-Lokt™			9 1/2		
R25063	120	Pointed Soft Point Core-Lokt™			9 1/2	24"	
Velocity (ft./sec.)							
Cartridge	Muzzle	100 yds.	200 yds.	300 yds.	400 yds.	500 yds.	
100 PSPCL	3230	2893	2580	2287	2014	1762	
120 PSPCL	2990	2730	2484	2252	2032	1825	
Energy (ft.-lbs.)							
Cartridge	Muzzle	100 yds.	200 yds.	300 yds.	400 yds.	500 yds.	
100 PSPCL	2316	1858	1478	1161	901	689	
120 PSPCL	2382	1985	1644	1351	1100	887	
Short-Range Trajectory *							
Cartridge	50 yds.	100 yds.	150 yds.	200 yds.	250 yds.	300 yds.	
100 PSPCL	-0.1	0.5	zero	-1.7	-4.6	-9.1	
120 PSPCL	0.1	0.6	zero	-1.9	-5.2	-10.1	
Long Range Trajectory *							
Cartridge	100 yds.	150 yds.	200 yds.	250 yds.	300 yds.	400 yds.	500 yds.
100 PSPCL	1.3	1.3	zero	-2.6	-6.6	-19.8	-41.7
120 PSPCL	1.6	1.4	zero	-2.8	-7.2	-21.4	-44.1

Note 1: Bullet does not rise more than 1" above line of sight from muzzle to sighting-in range.

Note 2: Bullet does not rise more than 3" above line of sight from muzzle to sighting-in range.

* Inches above or below line of sight. Hold low for positive numbers, high for negative numbers.